



Design Parameters

Road Type	BVA
Speed Limit	30 mph
Road Width	7.3 m
Longitudinal Safety Zone	
Shoulders Safety Zone	1.2 m
Taper Length (if applicable)	
Remaining Road Width	3m
Distance to First Sign	
Parking requires suspension	Y/N
Bus Stops Affected	Y/N
Permanent Signals Affected	Y/N

- Traffic Management Notes:**
- All temporary traffic management shall be in accordance with Chapter 5 of the Traffic Signs Manual 2009.
 - All temporary traffic management shall be in accordance with the Traffic Signs Regulations & General Directions 2016.
 - All Temporary Traffic Management Signs should be located at Street Works & Road Works: A Code of Practice 2013.
 - All Temporary Traffic Management Signs should be located 450mm minimum from the kerb face.
 - All temporary traffic management sign locations are indicative and are subject to on site approval from the Person in Charge.

Legend:

	Sign Face
	Cone
	Safety Zone
	Pedestrian Barrier
	Kerb Ramp
	Traffic Signal Head
	Pedestrian Signal Head
	Works Area
	Parking Restriction

NO.	REVISION	DATE
Client: LIGHTWAYS		
Site Address: HIGH STREET DAKLEITH		
Project: ROAD CLOSURE		
Title:	TM001	
JOB No.	DRAWN	DATE
DESIGNED	T Connor	12/05/2024
Scale	CHECKED	J Cooney
N.T.S	APPROVED	DATE
Dwg. No.	Revision	
TM001	A	

